

X3 F



X3.060 F - X3.070 F - X3.080 F-GE




McCORMICK

Power Technology.

		X3.060 F	X3.070 F	X3.080 F - GE
ENGINE				
Maximum power ISO	hp/kW	54.5 / 40	68 / 50	75 / 54.5
Rated power	rpm	2200		
Maximum torque	Nm	260	315	315
Engine type		2.5 Kohler KDI		
Stage V / Tier 4 Final exhaust gas after-treatment		EGR/DOC		
Cylinders / Displacement / Valves	cm ³	4 / 2.51 / 16		
Fuel tank capacity	l	50		
CLUTCH				
Type		11" - independent dry dual clutch		
Control		● mechanical		
TRANSMISSION				
No. of gears		● 12 FWD + 12 REV without creeper - ○ 16 FWD + 16 REV with creeper		
FRONT AXLE				
Traction		electro-hydraulic 4-wheel drive engagement		
Maximum steering angle		55°		
Rear differential lock		100% electro-hydraulic		
BRAKING SYSTEMS				
Front braking system		automatic four-wheel drive engagement while braking		
Rear braking system		wet multi-disc brakes		
Trailer braking system		○ hydraulic trailer braking or hydraulic braking according to MR and EEC directives		
HYDRAULIC SYSTEM				
Rear hitch hydraulic pump - flow rate	l/min	50		
Steering pump - flow rate	l/min	30		
Rear remote valves, type, min - max		mechanical, 1 - 3		
Mid-mounted remote valves		○ 1 rear remote valve with double outlets for mid-mount couplers		
Rear free flow return line with quick-coupling		○		
REAR 3-POINT HITCH				
Mechanically-controlled rear hitch		3-point hitch draft control, position control, mixed control, float position		
Length and width adjustment of lower links		○		
Standard lifting capacity	kg	● 2200		
Maximum lifting capacity with heavy-duty hitch and E.L.S. system	kg	○ 2200		
REAR PTO				
Type		mechanical		
Speeds	rpm	540 / 540+540E / 540+1000		
Rotation - spline shaft type		clockwise (viewed from tractor rear) - ● 1 3/8" shaft with 6 splines		
Ground speed PTO		●		
FRONT 3-POINT HITCH				
Maximum lifting capacity	kg	1000		
FRONT PTO				
Speed	rpm	1000		
CAB AND DRIVING POSITION				
Low-profile cab		○		
Air conditioning		●		
Digital instrument panel		●		
LED work lights for low-profile cab		○		
Iso-mounted platform		●		
DIMENSIONS AND WEIGHTS - MODELS WITH ROPS (IN RUNNING ORDER)				
Length 4WD	mm	3652		
Minimum width	mm	1358		
Wheelbase 4WD	mm	1950		
Minimum height over ROPS	mm	2214		
Minimum ground clearance 4WD	mm	186		
Weight 4WD in running order without ballast	kg	2200		
OPTIONAL EQUIPMENT				
6 front weights 24 kg each		○		

Key: ● standard ○ option

All data and illustrations provided in this brochure are for information purposes only and can be changed.